

# MX-ISEB05SM

## Surface Mounted Infrared Sensor

1. Different sizes available for different countries: European size 86\*86mm, ANSI Size 86\*55mm.
2. Red and Green colors LED indicator, red color when standby, green color when activated.
3. Time Delay: 0.3-30sec, Sensitive Distance: 3~15cm adjustable.
4. Fireproof ABC material Faceplate, elegant design with safety handle.



## Overview

MX-ISEB05SM series IR Sensor No Touch Touchless exit button is use ABS plastic plate and able to make waterproof. It's easy-to-install and most frequently used in the access control systems. The superior design of the buttons and quality construction offer outstanding performance for years, becoming a classic style.

Similar to NF-C series touchless exit button is IR Sensor technology with 5 cables included for NO (Normal Open), NC (Normal Close) and COM (Common) and +12V DC and GND, it has red and green double colors LED indicator. Red color when standby and Green color when activated.

55\*86mm Square size is hot sell items in American and 86\*86mm Square European size is hot sell items in European and Asian as well as other countries at this size.

## Features

1. Different sizes available for different countries: European size 86\*86mm, ANSI Size 86\*55mm.
2. No Touch sign or Hand Symbol, different faceplates to meet different requirements.
3. Red and Green colors LED indicator, red color when standby, green color when activated.
4. Time Delay: 0.3-30sec, Sensitive Distance: 3~15cm adjustable.
5. Fireproof ABC material Faceplate, elegant design with safety handle.



## MX-ISEB05SM

## Surface Mounted Infrared Sensor

### Specification

Model	MX-ISEB05SM
Panel Material:	Fireproof ABC material
Input Voltage	3A @ 12VDC-28VDC
LED Indicator	Red LED indicator / Power ON (Standby) Green LED indicator / Power ON (Sensation)
Output Contact	NO/NC/COM
Current Rating	12-28V,3A
Output Contact	NO,NC,COM
Sensitive Distance	3~15cm adjustable
Time Delay	0.3-30sec adjustable
Mechanical Life	500,000 tested
Waterproof protection	IP-55
Option	Waterproof IP68 Can be customized
Operating Temperature	-20°C~60°C
Operating Temperature	-20~95%
Operating Humidity	0~95%
Dimensions	86*55*20 (mm)
Weight	100pcs/52*43*32cm/10.5kg/ctn

