

MX-350MSW

Waterproof Electromagnetic Lock

- Voltage:DC12V or DC24V.
- Waterproof IP68.
- Holding Force: 180kg (350Lbs).
- Lock Size: 220L*36W*21H(mm).
- Armature Plate:130L*33W*9.3H(mm).
- Current Draw: 12V/500mA 24V/250mA.
- With Timer & Buzzer Customization Available.



Overview

MX-350MSW single door 350Lbs Waterproof Electromagnetic Lock, specially used to out glass door, wooden door, metal door, fire doors, and all kinds of door. Hoisting design, saves time and power when installation. Inward door, frameless glass door, narrow door all have a complete set of accessories. Special Anti-residual magnetic design makes automatic access control safer.

Features

- 1.Wear materials, durable.
- 2.waterproof, whole sealing treatment.
- 3. Suitable for Indoor and outdoor.
- 4. Anti-residual magnetic design, keep constant tension.
- 5. Electromagnetic suction work completely, there is no mechanical failure.
- 6.Shell with high strength alloy material, anode hardening treatment.
- 7.lock body with double insulation treatment.
- 8. Through the European CE and ROHS, MA certification in China.
- 9. Waterproof, outdoor magnetic lock, passed 350lbs super static linear tension tests.
- 10. Built-in reverse current protection device (MOV), performance stability, safety coefficient is higher.







MX-350MSW

Waterproof Electromagnetic Lock

Specification

| Model | MX-350MSW |
|---------------------------------------|--|
| Holding Force | 180kg (350Lbs) |
| Waterproof grade | IP68 |
| LED | NO |
| Lock Status Sensors | Dry contact NO, NC, COM |
| Rated Operating Voltage | 12/24VDC |
| Current consumption | 12V/500mA 24V/250mA |
| Optional Functions | Relock Delay Timer, Buzzer |
| Surface finish for magnet | Zinc plated |
| Surface finish for armature plate | Zinc plated |
| Ambient temperature in °C | -10∼+55°C (14-131F) |
| Suitable for | Wooden & Aluminum & Glass & Fireproof &Metal |
| Magnets Dimensions (L x W x D) | 220Lx36Wx21H (mm) |
| Armature Plate Dimensions (L x W x D) | 130L*33W*9.3H (mm) |
| Weight in kg | 1.3kg |
| CE-mark for building | Yes |
| Rohs-mark for building | Yes |



